

TECHSELECT® MULTI-PURPOSE AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

TechSelect® Multi-Purpose Automatic Transmission Fluid (ATF) is a multi-functional transmission fluid for passenger cars, trucks, construction and mining equipment, farm machinery and other mobile and industrial systems. TechSelect® Multi-Purpose Automatic Transmission Fluid (ATF) is blended with highly refined base oils and offers many performance benefits, including superior cold temperature performance characteristics, wide range of seal compatibility, excellent wear protection, superior frictional characteristics with excellent friction retention and smooth shifting. It also has excellent corrosion and rust preventive properties, as well as rigid anti-foam characteristics. It will not cause excessive seal swell or shrinkage, nor will seals excessively harden or soften.

PERFORMANCE BENEFITS:

This product is recommended for use in automatic transmissions manufactured by General Motors and Ford for model years 2006 and prior (except those requiring Ford Type F, Mercon V and SP, Dexron VI and CVT fluids). This product is suitable for use in powershift transmissions, torque converters, hydrostatic transmissions and applications such as in air compressors, hydraulic pumps, power steering boxes and other types of service where an ATF is recommended.

Suitable for use in applicable pre-2006 GM and pre-2007 Ford automatic transmissions. Not recommended for transmissions requiring Ford Type F ATF, Mercon V and SP, Dexron VI and CVT fluids.

TYPICAL PROPERTIES:

Property	ASTM Test Method	
Viscosity @ 40°C, cSt	D445	30.99
Viscosity @ 100°C, cSt	D445	7.14
Viscosity Index	D2270	205
Flash Point, COC, °C	D92	208
Flash Point, COC, °F	D92	406
Pour Point, °C	D97	-48
Pour Point, °F	D97	-54
Color	D1500	Red
Gravity, °API	D4052	32.9



Updated: 09/2014

TSUNMPATF