

## TECHSELECT® PREMIUM SYNTHETIC BLEND MOTOR OILS

**DESCRIPTION:** TechSelect® Synthetic Blend Engine Oils are blended with highly refined base oils and contain a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins. TechSelect® Synthetic Blend Engine Oils also protect engines from sludge, rust and acid build-up. These oils perform efficiently in gasoline engines and are outstanding for stop-and-go taxi fleets, city delivery vehicles and public utility fleets.

**PERFORMANCE BENEFITS:** Meets or exceeds the following tests and requirements:  
 API Service Classification - SN, ILSAC GF-5  
 Chrysler MS-11999, MS-12007, MS-12015  
 Resource Conserving  
 Ford Motor Company - WSS-92C945-A, WSS-92C946-A  
 Honda  
 Toyota

TYPICAL PROPERTIES:	ASTM Test			
	Method	SAE 5W20	SAE 5W30	SAE 10W30
Viscosity @ -30°C, cP	D5293	5000	6100	N/A
Viscosity @ -25°C, cP	D5293	N/A	N/A	5700
Viscosity @ 40°C, cSt	D445	46.0	64.0	68.0
Viscosity @ 100°C, cSt	D445	8.2	10.6	10.4
Viscosity Index	D2270	152	157	140
Flash Point, COC, °C	D92	229	231	231
Flash Point, COC, °F	D92	421	448	448
Pour Point, °C	D97	-40.0	-40.0	-36.0
Pour Point, °F	D97	-40.0	-40.0	-33.0
Color	D1500	3.0	3.0	2.5
Gravity, °API	D4052	32.8	32.6	29.5
HT/ HS, cP	D4683	2.6	3.1	3.0



Updated: 09/2014

TSUNSBPCMO